

Mobile BLUETOOTH®-/ IRDA printer

Suitable for

testo 300, testo 310, testo 417, testo 512-1,
testo 512-2, testo 416, testo 425, testo 625,
testo 110, testo 535, testo 925, testo 922,
testo 545, testo 400, testo 440 dP, testo 440

Mobile BT®/ IRDA printer

Order no. 0554 0622

Technical data

Model	Mobile BT/IRDA printer
Printing speed	30 mm/s
Operating temperature	0 to +50 °C / 32 to 122 °F
Storage temperature	-20 to +50 °C / -4 to 122 °F
Dimensions (LxWxH)	150 mm x 80 mm x 41 mm
Weight	approx. 400 g (including rechargeable battery pack, paper roll, mains unit)
EU Directive	2014/53/EC
Power supply	Lithium-Ion rechargeable battery pack, 3500 mAh, 3.7 V
Thermal paper roll	56.5 mm x 34 mm x 12 mm
Rechargeable battery storage temperature	±0 to 35 °C / 32 to 95 °F
Rechargeable battery charge time	approx. 6 to 8.5 h
Rechargeable battery life	> 6 h (20 °C / 68 °F ambient temperature)
Warranty	2 years (excl. printer mechanism, rechargeable battery pack)
Warranty terms	Warranty terms: see website www.testo.com/warranty



Accessories/spare parts

Part no.

Mains unit 5 V / 1.0 A	0554 1105	
Spare thermal paper, 6 rolls	0554 0568	