

Data sheet

testo 174 T / testo 174 T BT
testo 174 H / testo 174 H BT



Mini data logger for temperature and humidity

testo 174 T / testo 174 H
with USB-C and PC software



Broad temperature measuring range from -22 to 158 °F (-30 °C to +70 °C)

Fast and uncomplicated data readout via USB-C

Professional software for Excel export, logger programming, data analysis and PDF reporting

Precise measurement of humidity and temperature in the range from -4 to 158 °F (-20 °C to +70 °C)

Reliable automatic data backup in the event of an empty battery or battery change; convenient storage of up to 16,000 measured values



testo 174 T BT / testo 174 H BT
with Bluetooth and app connection



Broad temperature measuring range from -22 to 158 °F (-30 °C to +70 °C)

Free testoSmart App includes export function and report generation

Precise measurement of humidity and temperature in the range from -4 °F to 158 °F (-20 °C to +70 °C)

Simple and intuitive configuration as well as analysis of measurement data with the testo Smart App

Reliable automatic data backup in the event of a flat battery or battery change; convenient storage of up to 16,000 measured values



The testo 174 mini data logger instruments are ideal for continuous monitoring temperature and humidity-sensitive goods in warehouses, restaurants and building climate with food in mind thanks to HACCP and NSF certifications. The testo 174 H and testo 174 H BT loggers measure temperature and humidity, while the testo 174 T and testo 174 T BT focus on temperature. All models store up to 16,000 values and protect against data loss with automatic backup during battery changes.

The free ComSoft Basic software allows quick setup and easy data analysis, including Excel export and PDF reports. ComSoft


Professional provides advanced features for trend analysis, multi-location reports, and secure archiving. All for the 174 H and 174 T loggers.

Bluetooth models (174 H BT and 174 T BT) offer convenient operation via the testo Smart App, available for iOS and Android. The app lets you view measurements, create PDF reports, add photos/comments, and email results directly from your smartphone or tablet. These reliable, cost-effective loggers deliver precise data and support compliance with quality assurance standards.

Mini temperature data logger


testo 174 T

Mini temperature data logger with PC software testo 174 T, 1 channel, includes wall bracket, batteries (2 x CR2032 Lithium) and test report



Order no. 0572 1740 01

USB-C





testo 174 T BT

Mini temperature data logger with app connection testo 174 T BT, 1 channel, includes wall bracket, batteries (2 x CR2032 Lithium) and test report



Order no. 0572 1742 01



	testo 174 T	testo 174 T BT
Sensor type	NTC	Digital
Measuring range	-22 to 158 °F (-30 to +70 °C)	
Accuracy ±1 digit	±0.9 °F (-22 to 158 °F) (±0.5 °C (-30 to +70 °C))	
Solution	0.1 °F / °C	
General technical data		
Channels	1 x internal	
Battery type	2 Lithium batteries (CR 2032)	
Battery life	500 days (15 min. measuring cycle, 77 °F (+25 °C))	
Operating temperature	-22 to 158 °F (-30 to +70 °C)	
Storage temperature	-40 to 158 °F (-40 to +70 °C)	
Dimensions	2.4 X 1.5 X 0.7 in (60 X 38 X 18.5mm)	
Weight	1.2 oz (35g)	
Certification	EN12830, HACCP, NSF	
Protection class	IP65	
Measuring cycle	1 min to 24 h	
Memory	16,000 readings	
Connection/connector	USB 2.0 / USB C	Bluetooth
Software	 testo ComSoft Basic testo ComSoft Professional	 testo Smart App
Logger configuration	✓	
Measurement data evaluation	✓	
Reporting	✓	✓ (only possible after registration)
Measurement data export	PDF / XLS / HTML / CSV	PDF / CSV / JSN

Mini data logger for temperature and humidity

testo 174 H

Mini data logger testo 174 H for temperature and humidity with PC software, 2 channel, incl. wall bracket, batteries (2 x CR 2032 lithium) and test report



Order no. 0572 1741 01

USB-C

testo ComSoft PROF

testo ComSoft BASIC

testo 174 H BT

Mini data logger testo 174 H BT for temperature and humidity with app connection, 2 channel, incl. wall bracket, batteries (2 x CR 2032 lithium) and test report






Order no. 0572 1743 01

Bluetooth

testo SMART

	testo 174 H NTC	testo 174 H BT Digital
Sensor type	NTC	Digital
Measuring range	-4 to 158 °F (-20 to +70 °C)	
Accuracy ±1 digit	±0.9 °F (-4 to 158 °F) (±0.5 °C (-20 to +70 °C))	
Resolution	0.1 °F / °C	
Sensor type	Testo humidity sensor, capacitive	
Measuring range	0 to 100 %RH*	
Accuracy ±1 digit	±3 %RH (2 to 98 %RH) ±0.03 %RH/K	
Resolution	0.1 %RH	

* Not for condensing atmospheres. For continuous application in high humidity (>80 %RH at ≤86 °F (30 °C) for >12 h, >60 %RH at >86 °F (30 °C)) for >12 h, please contact us via our website.


General technical data		
Channels	2 x internal	
Battery type	2 Lithium batteries (CR 2032)	
Battery life	1 year (15 min. measuring cycle, 77 °C (+25 °C))	
Operating temperature	-4 to 158 °F (-20 to +70 °C)	
Storage temperature	-40 to 158 °F (-40 to +70 °C)	
Dimensions	2.4 X 1.5 X 0.7 in (60 X 38 X 18.5mm)	
Weight	1.2 oz (35g)	
Certification	HACCP	
Protection class	IP20	
Measuring cycle	1 min to 24 h	
Memory	16,000 readings	
Connection/connector	USB 2.0	Bluetooth
Software	  testo ComSoft Basic testo ComSoft Professional	 testo Smart App
Logger configuration	✓	
Measurement data evaluation	✓	
Reporting	✓	✓ (only possible after registration)
Measurement data export	PDF / XLS / HTML / CSV	PDF / CSV / JSN

Accessories

ComSoft Basic

Free download

Basic software for programming and reading out Testo data loggers; display of measured values in graph and chart form, and export function.



Order no. 0572 0580



testo Smart App


Free download

The app turns your smartphone/tablet into the display for the testo 174 T BT / testo 174 H BT. The operation of the measuring instrument and the display of the measured values are by Bluetooth® via the testo Smart App on your smartphone or tablet – irrespective of the measuring location. In addition, you can use the App to create measurement reports, add photos and comments to these and send them by e-mail. For iOS and Android.



ComSoft Professional

Expert software for programming and reading out Testo data loggers, as well as for additional needs like combining measurement data produced at many places, including data preservation.



Order no. 0554 1704



Accessories for all versions of testo 174

Order no.

Lithium battery CR 2032 button cell (please order 2 batteries per logger)	0515 5174	
ISO temperature calibration certificate; calibration points -18°C, 0°C, +40 °C; per channel/instrument	0520 0153	

Accessories for testo 174 T and testo 174 H


Order no.

ComSoft Basic, basic software for programming and reading out Testo data loggers; display of measured values in graph and chart form, and export function. Available as a download after registration.	0572 0580	
ComSoft Professional, professional software, including data archiving	0554 1704	

Accessories for testo 174 H and testo 174 H BT

Order no.

ISO humidity calibration certificate; calibration points 11.3 %RH and 75.3 %RH at +25 °C/+77 °F; per channel/instrument	0520 0076	
-------------------------------------------------------------------------------------------------------------------------	-----------	--



0981 0334/msp/09.2024

Subject to change, including technical modifications.